



قابلیت‌ها

- رزولوشن ۶ مگاپیکسلی ۲۰ فریم بر ثانیه
- پشتیبانی از فرمت های فشرده سازی H.265+/H.265/H.264
- پشتیبانی از تحلیل هوشمند : نفوذ به منطقه، پرسه زنی، تشخیص عبور از خط، تشخیص وسایل نقلیه غیرقانونی، تشخیص غیبت، تشخیص حرکت بر خلاف جهت مجاز تعریف شده
- بدنه ضد آب و گرد و غبار با درجه IP۶۷
- پشتیبانی از پروتکل ONVIF و پروتکل انحصاری SLINK
- پشتیبانی از ضبط اضطراری ANR
- وب نویسی به زبان فارسی و انگلیسی

Features

Camera	
Sensor	1/2.8", 6MP progressive scan low illumination COMS
Lens	2.8 mm Fix Lens
Minimum Illumination	Color: 0.001Lux (AGC ON)
IR Range	IR distance is 60 m and the max. warm light distance is 40 m
D&N	ICR switch, auto/color/B&W/CDS trigger/customized time
D-WDR	Support
3D DNR	Off/Low/Middle/High/Higher
Defog	Off/Low/Middle/High
Mirror	Off/horizontal mirror/vertical mirror/180° flip
Image Setting	Brightness, contrast, sharpness, saturation, chroma
Video / Audio	
Video Compression	H.265+/H.265/H.264+/H.264/Mpeg4/jpeg/Mjpeg
Frame Rate	Main stream: 6MP (3200*1800@20fps), 4MP(2560*1440@25fps), 3MP(2304*1296@25fps), 2MP(1920*1080@25fps) Sub Stream: D1(720*576)@25fps,VGA(640*480)@25fps,Q720P(640*360)@25fps,864*480@25fps
Video Code Rate	Fixed code rate, variable code rate
Video Type	Composited stream/video stream
Audio Standard	G.711u/G.711A 8K 64bit
Motion Detection	Set detection area, can set multi-level sensitivity
Occlusion Alarm	Support 1 area
Privacy Mask	Support 4 areas
Schedule Linkage	Upload Email upload picture , Arming time support day arming/ night arming /customized arming
Device Abnormal Inspection	Support disconnection alarm, IP conflict alarm, illegal access alarm
Character Overlay (OSD)	Support time OSD/Title OSD, multi-line OSD (two lines) Main stream font support 12-60pt, sub stream font support 12-36pt
Audio	MIC Input/ Output
Amplifier	Built-in amplifier
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP,RTMP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x , IP Filtering , SNMP, QoS,Multicast
Network Storage	ANR, FTP, NAS
Compatible Integration	Onvif, GB28181
Network	1 RJ45 10M/100M Base-TX Ethernet
Phone monitoring	Support mobile phone monitoring (iOS, Android)
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
Working Environment	-10°C ~ 50°C
MTBF	150,000 Hours
Reset Button	Supported
Ingress Protection	IP67
Vandal Resistant	IK10