



قابلیت‌ها

- رزولوشن ۸ مگاپیکسلی ۲۵ فریم بر ثانیه
- پشتیبانی از فرمت های فشرده سازی H.۲۶۴ / H.۲۶۵ / H.۲۶۵+
- پشتیبانی از تحلیل هوشمند : نفوذ به منطقه، پرسه زنی، تشخیص عبور از خط، تشخیص وسایل نقلیه غیرقانونی، تشخیص غیبت، تشخیص حرکت بر خلاف جهت مجاز تعریف شده
- بدنه ضد آب و گرد و غبار با درجه IP۶۷
- پشتیبانی از پروتکل ONVIF و پروتکل انحصاری SLINK
- پشتیبانی از ضبط اضطراری ANR
- وب نویسی به زبان فارسی و انگلیسی

Features

Camera	
Sensor	1/2.7", 8MP low illumination CMOS sensor
Lens	2.8 mm Fix Lens
Minimum Illumination	Color: 0.001Lux (AGC ON)
IR Range	IR distance is 40 m and the max. warm light distance is 30 m
D&N	ICR switch, auto/color/B&W/CDS trigger/customized time
D-WDR	Support
3D DNR	Off/Low/Middle/High/Higher
Defog	Off/Low/Middle/High
Mirror	Off/horizontal mirror/vertical mirror/180° flip
Image Setting	Brightness, contrast, sharpness, saturation, chroma
Video / Audio	
Video Compression	H.265+/H.265/H.264+/H.264/Mpeg4/Jpeg/Mjpeg
Frame Rate	Main stream: 8MP(3840*2160@25fps), 5MP (2592*1904@25fps), 4MP(2560*1440@25fps), 3MP(2304*1296@25fps), 2MP(1920*1080@25fps) Sub Stream: D1(720*576)@25fps,VGA(640*480)@25fps,Q720P(640*360)@25fps, 864*480@25fps
Video Code Rate	Fixed code rate, variable code rate
Video Type	Composited stream/video stream
Audio Standard	G.711u/G.711A 8K 64bit
Motion Detection	Set detection area, can set multi-level sensitivity
Occlusion Alarm	Support 1 area
Privacy Mask	Support 4 areas
Schedule Linkage	Upload Email upload picture, Arming time support day arming/ night arming /customized arming
Device Abnormal Inspection	Support disconnection alarm, IP conflict alarm, illegal access alarm
Character Overlay (OSD)	Support time OSD/Title OSD, multi-line OSD (two lines) Main stream font support 12-60pt, sub stream font support 12-36pt
Audio	MIC Input/ Output
Amplifier	Built-in amplifier
Network	
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTMP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, IP Filtering, SNMP, QoS, Multicast
Network Storage	ANR, FTP, NAS
Compatible Integration	Onvif, GB28181
Network	1 RJ45 10M/100M Base-TX Ethernet
Phone monitoring	Support mobile phone monitoring (iOS, Android)
General	
Power	DC 12V±25%, PoE (IEEE 802.3af)
Working Environment	-10°C ~ 50°C
MTBF	150,000 Hours
Reset Button	Supported
Ingress Protection	IP67
Vandal Resistant	IK10